



THE ORIGINAL  
**MORRIS & Co**

FOUNDED BY WILLIAM MORRIS IN 1861

**PAINT**  
**CHALKY MATT**

**CHARACTER**

Gorgeously flat and with a great depth of colour, Chalky Matt Emulsion from Morris & Co. Paint offers the perfect heritage hue with each brushstroke. Made with only premium ingredients that are planet-friendly, Chalky Matt's washable finish leaves an enduringly harmonious look.

Made for the modern craftsperson with colours sourced from the Morris & Co. archive, Chalky Matt is ideal for enveloping walls and ceilings in a timeless Morris & Co. palette.

**LOOK FORWARD TO**

- Minimal drying time of just two hours
- Strong scrub resistance, perfect for busy homes
- Reduced residual brush marks and cutting in, leaving an unblemished heritage look
- Self-priming on most surfaces

**PREPARATION**

All surfaces to be painted should be clean, dry and free from loose and flaking material including dirt and grease. Prime bare metal surfaces with an appropriate primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust and wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces as they may contain harmful lead.

**APPLICATION**

Stir well before use. Ensure good ventilation during application and drying. Apply by brush, roller or sprayer. Do not overfill paint trays. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading. Apply two coats. Additional coats may be required on new plaster or where a greater colour change is desired. Do not apply in temperatures below 10°C or in damp conditions. If more than one can of colour is to be used in the same area, intermix before use.

**CLEANING**

Remove as much product as possible from equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses.

**HEALTH & SAFETY**

• Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-octyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one. May produce an allergic reaction. Safety data sheet available on request.

- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.

**RECOMMENDED USES**

Suitable for commercial and residential spaces.

**TYPE OF SUBSTRATE**

Interior walls, ceilings, woodwork, suitably prepared metal and radiators.

**COLOUR RANGE**

Morris & Co Paint - 40 colours.

**FINISH**

Minimal sheen - 2%.

**VOLUME SOLID**

35.2%.

**COVERAGE**

One coat of Morris Chalky Matt Emulsion covers up to 14m<sup>2</sup> per litre, depending on the nature and porosity of the surface.

**DRYING TIME**

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

**TRANSPORTATION & STORAGE**

To avoid the risk of spillage, always store and transport in a secure upright position.

Protect from frost, store away from heat and flame.

**CLEANER**

Clean water.

**VOC CONTENT**

- Low VOC (Volatile Organic Compounds) Content 0.3 - 7.99%.
- EU limit value for this product Cat A/(a): 30 g/L (2010).
- This product contains max 8g/1 VOC.

**FILM THICKNESS**

Wet: 86µm, Dry: 30µm.

**SIZES**

2.5 Litre, 5 Litre.